

iFace 402



➤ Multi-biometric Identification Time Attendance & Access Control Terminal

CPU : Multi-Bio CPU-800 MHz
Memory : 256MB Flash, 64MB SD RAM
Camera : High Resolution Infrared Camera
Display : 4.3" TFT Touch Screen
Fingerprint Sensor : 500DPI Optical Sensor
Face Capacity : 500 (1:N), 3000 (1 :1)
Fingerprint Capacity : 2000
Transaction Capacity : 1,00,000
Algorithm Version : Face 5.0 and Finger 10.0 Version
Inbuilt Proximity Card Reader
Communication : TCP/IP , RS232/485 , Two USB-Host
Access Control Interfaces For : EM Lock , Door Sensor,
Exit button
Wiegand Signal : Output
Power Supply : 12V , 3A
Verification Speed : <= 2 sec
Operating Temperature : 0°C - 45°C
Operating Humidity : 20% - 80%
Dimension(LxWxT) : 193.6 x 146.8 x 111 mm

Standard Functions:

- ▶ ID Card
- ▶ Automatic Status Switch
- ▶ Self Service Query
- ▶ Work Code
- ▶ T9 Input
- ▶ 9 Digit User ID

Optional Features:

- ▶ Mifare Card
- ▶ Web server, GPRS, Wi-Fi
- ▶ Short Message