



## VF 380



### ➔ Multibiometric Identification Time & Attendance and Access Control Terminal

Face Capacity : 200(1:N)  
ID Card Capacity : 10,000  
Logs Capacity : 100,000  
Image Sensor : Special Sterio Dual Sensor  
Algorithm : 7.0 Version  
Communication : TCP/IP , USB- Host , USB-client  
Verification Speed :  $\leq 1$ sec  
FAR :  $\leq 0.0001\%$   
FRR :  $\leq 1\%$   
Operating Temperature :  $0^{\circ}\text{C} - 45^{\circ}\text{C}$   
Operating Humidity : 20% - 80%  
Power : 12V , 1.5A  
Display : 3" TFT Touch Screen  
Dimensions(LxHxW) : 104.70 x 160.00 x 36.00 mm

Access control interfaces for : 3rd party electric lock ,  
Door Sensor , Exit button  
Standard Functions : ID Card , Automatic Status Switch  
Self Service Query , Work code , T9 Input , DLST  
9 digit user ID , Scheduled bell

#### Features:

Elegant ergonomic design  
Face , RFID , PIN identification mode  
TCP/IP communication and USB-host  
3" TFT screen , infra red optical system enables user  
identification in poor lit environment  
Optional mifare card module