

PIR LIGHT SWITCHS

A-ES7



A-ES7 : 2000 W Occupancy detector,360° micro motion detector, Ceiling flush mount, Photo sensor inside for smart control, Run-on time adjustable Ambient lux. setting adjustable, Up to 1500W loading for fluorescent (T8), Smart Relay™ inside to protect product life.

SPECIFICATIONS

Power requirement	: 220 ~ 240VAC / 50Hz
Loading	: 2,000W for resistance
Power Usage	: 2,000W for halogen & incandescent 1,500W for fluorescent (T8)
Detection Angle	: 360°
@2.5m height	: $\Phi= 6m$ for micro motion, $\Phi= 12m$ for walk across motion
Run-on time setting	: 10 sec. ~ 40 min,
Ambient light setting	: 30 ~ 200 Lux.
Operation mode	: Auto
Warm-up time	: Approximately 1 minute
Smart Relay	: Yes (Ver2.0+)
Isolation Protection	: Class II

Water proof : IP20
Working temp. : -10°C~+40°C
Storage temp. : -20°C~+70°C
Power consumption : 1W maximum
Dimension (W*L*D) : Φ 86mm * 74.5mm depth

APPLICATION AREA

Car Park , Corridor, Dining Area, Individual Cabins, Large Cabins, Lift Lobby, Lifts, Living Room, Lobbies, Meeting Rooms, Pantry, Reception Areas, Rest Room, Small Offices, Stairways, Stores, Veranda.