

Vari-Focal Dome Camera with OSD

Main Features

- ⇒ 1/3" Sony Super HAD II CCD
- ⇒ 480TVL Standard Resolution Camera
- ⇒ 0.1lux @ F1.2
- ⇒ 4~9 mm Vari-Focal Auto Iris Lens
- ⇒ AGC, AWB, BLC, OSD
- ⇒ CE, FCC and RoHS Certified



Feature	Specification
Image Sensor	1/3" Sony Super HAD II CCD
Pixels	PAL:537Hx597V, NTSC:537Hx505V
Resolution	480TVL
Min. Illumination	0.1lux @F1.2
S/N Ratio	more than 48dB
Electronic Shutter	NTSC:1/60 ~1/100,000 sec PAL: 1/50 ~1/100,000 sec
Flickerless Mode	EE/AI
Iris Control	Auto
Lens	4~9 mm
Focus Mode	Manual
Gamma Correction	>0.45
White Balance (AWB)	ON/OFF Selectable
Gain Control (AGC)	ON/OFF Selectable
Back Light Compensation	ON/OFF Selectable
Day & Night (ICR)	Auto/Color/B&W
Sync	Internal
Video Output	1.0 Vp-p/75 ohm
Special Functions	OSD
Power Supply	DC 12V ± 5%
Power Consumption	<2W
Dimensions	76.2 x 102
Weight	300
Operating Temperature	-10~50 °C
Certifications	CE, FCC, RoHs