

AVTRON**MONARCH 27X & 12X****AM-CD127-OS27****HIGH SPEED DOME OS27  
DI IP PTZ CAMERA****Superior Engineering Design & Sensational Image Quality**

## **AM-CD127-OS27 HIGH SPEED DOME OS27 DI IP PTZ CAMERA**

### **Features :**

- 1/3" CCD Image Sensor Reach up to Full D1 Resolution
- High Resolution 500TVL@Color & 570TVL@B/W
- 324X Zooming by Optical 27X & Digital 12X
- 127 Preset, 4 Patterns, 8 Swing & Groups Function
- Duplex Compression Streaming H.264, MJPEG for Network, Record
- Compliant with ONVIF 2.0 on May, 2012
- "Common Gateway Information API for 3rd party intrigration CMS/VAS/NVR "
- Low illumination 0.7Lux @ Color, 0.02Lux@B/W, 50IRE-F1.2
- Built in Fan/Heater
- Lightening Speed 360. /Sec & Smooth Manual Speed Min 0.05./sec
- Video Loss alarm for Continous monitoring & illegal Disconnection
- Compatible with AVTRON Free Software Live up to 36CH with 16CH Playback Support
- Built in Multicast Streaming by that Large number of User can log on with Sensible Video Quality
- Wide Range Supported Network Protocol TCP/IP, UDP, RTP, RTSP, HTTP,DHCP, FTP, SNMP, DNS, DDNS
- Firmware Upgradeable Via IP Network
- Support 1CH Audio in/out Communication (G.711/AAC)
- OSD Menu Control BY Confrigration Menu
- Adjustable Exposure Mode Auto/Flicker/ Manual, Sense-Up
- Support Email Notification, FTP Upload, Composite Video Output
- 3rd party System intrigration by RS485/Sensor/Relay
- Motion Detection,BLC, Privacy Masking, Camera ID & etc
- Dual Power Support by 12V DC & POE
- Weatherproof IP 67 Proction with Compact Dome Enclosure



## Specifications :

|                                |  |
|--------------------------------|--|
| Model No.                      | AM-CD1127-OS27                                   |
| <b>Camera Specification</b>    |  |
| CCD Type                       | 1/3" Double Scan CCD Image Sensor                |
| Effective Pixels               | PAL : 752(H)x582(V), NTSC : 768(H)x494(V)        |
| Tvline Resolution              | 550TVL @ Color, 680TVL @ B/W                     |
| Lux Level(illumination)        | 0.4 Lux @ Color, 0.02 Lux @ (B/W), @ F1.6, 50IRE |
| Shutter Speed Control          | AUTO / Manual: 1/4s ~ 1/10,000s                  |
| Gain Control(AGC)              | AUTO / Manual: 0 ~ 50dB                          |
| Lens                           | F = 3.5mm ~ 94.5mm, @ F1.6(Wide) ~ F2.9(Tele)    |
| Zoom Ratio                     | 27X Optical / 12X Digital                        |
| Focus Control                  | Auto / Manual / Semi-Auto                        |
| White Balance                  | Auto / Manual(Red, Blue, Gain Adjustable)        |
| ICR Filter                     | YES  |
| <b>On Screen Display</b>       |  |
| WDR                            | YES, On/Off                                      |
| Day/Night                      | On/Off   |
| Flickerless                    | On/Off   |
| Sens-Up                        | up to 8X   |
| Back Light Compensation(BLC)   | BLC / HLC /Off                                   |
| Camera ID Name                 | On/Off   |
| OSD Menu Control               | By Confrigation Menu                             |
| Privacy Masking                | Off / On : 8 Zone                                |
| Digital Slow Shutter           | X2 / X4 / X8 Field                               |
| <b>Compression/Video/Audio</b> |  |
| Video Compression              | H.264 / MJPEG                                    |
| Video Resolution               | NTSC : 720x480, 720x420, 352x480, 352x420        |
|                                | PAL : 720x576, 720x488, 352x576, 352x288         |
| Record & Live Frame rate       | Selectable 1 ~ 30fps @ Full D1                   |
| Bit Rate                       | 32Kbps ~ 4MBPS                                   |
| Video output                   | Composite / RJ-45                                |

## Specifications :

|                              |   |
|------------------------------|---|
| Audio Compression            | G.711u(64kbps), AAC(28kbps)                               |
| Audio Connection             | Line in / Line out (Stereo JACK)                          |
| Communication                | Bi-directional  |
| <b>Software Intrigration</b> |   |
| Onvif                        | YES, V2.0   |
| CMS Record                   | CAMMANAGER 36CH Record                                    |
| CMS Playback                 | 16CH Playback Support                                     |
| 3rd Party VMS/NVR /CMS       | BY Onvif V2.0 / CGI                                       |
| Event Trigger                | BY Motion detection, Alarm Port                           |
| Event Handing                | On-screen alerts/Mail/FTP/Configurable alert sound/Record |
| Event Recording              | Pre-record (3sec.)/Post-record (30sec.)                   |
| FTP Upload                   | YES   |
| EMAIL Notifiacion            | YES   |
| <b>Memory &amp; Storage</b>  |   |
| DDR RAM                      | 1 GB  |
| FLASH RAM                    | 1 GB  |
| <b>Network</b>               |   |
| Connection                   | RJ-45 Ethernet  |
| Protocol                     | TCP/IP, UDP, RTP, RTSP, HTTP, DHCP, FTP, SMTP, DDNS       |
| Streaming                    | Unicast, Multicast  |
| LAN Connectivity             | 10/100 Based-T  |
| <b>Pan/Tilt</b>              |   |
| Pan/Tilt Range               | Pan : 360.(Endless) / Tilt : 95.                          |
| Pan/Tilt Speed               | Manual : 0.05. ~ 360./Sec, Swing : 1. ~ 180. /Sec         |
| Preset                       | 127 Present   |
| Patterns                     | 4 Patterns  |
| Swing                        | 8 Swings  |
| Group                        | 8 Group ( Max 80 Enteries for Each Group)                 |
| <b>Interface</b>             |   |
| RS-485                       | Yes, Pelco-D, Pelco-P Selectable                          |

## Specifications :

|                       |                               |
|-----------------------|-------------------------------|
| Sensor                | 4 x Sensor Input              |
| Alarm                 | 2 x Alarm Output(Relay)       |
| <b>General</b>        |                               |
| Power Supply          | PoE, IEEE802.3af & DC 12V     |
| Power Consumption     | <3 Amp                        |
| IP Protection         | IP 67                         |
| FAN/ Heater           | YES                           |
| Heater Temp           | Start From 10.C ~ 30.C ~ 60.C |
| Operating Temperature | -0°C ~ + 50°C                 |
| Operating Humidity    | 30% ~ 80% RH                  |
| <b>Mechanical</b>     |                               |
| Weight (g)            | 6Kg Approx.                   |
| Dome                  | Poly Carbonate Dome Cover     |
| Housing               | Alluminum                     |

\* Product specifications and appearance may be changed without prior notice due to improvements.



Scan with your  
Smart phone for  
more information  
[www.asi.ind.in](http://www.asi.ind.in)