

## BE-4714DMFP

H.264, 1.4 MP IP Mini Vandal Dome



Low  
Light

### Features :

- 1/3" 1.4 MP Sony Progressive CMOS sensor
- H.264 Main Profile & MJPEG dual-stream
- Max 25/30fps@720P (1280x1024, 1280x720)
- Digital WDR, 2D , 3D NR, AWB, AGC, BLC
- Fixed Lens 2.6mm, 4mm , 6mm or 8mm.
- Multiple Network Monitoring: Web viewer, CMS, Smart phone.
- Manual Pan 90°, Manual Tilt 90°
- Support defogging
- Support image rotation 90° or 270°
- POE optional
- Micro SD Card Slot
- BNC Video Output (for installation)
- 3-Axis Rotational
- Micro SD Card Slot (max 64GB)
- Built-in POE

### Specifications :

Image Sensor	1/3" 1.4 Megapixel Sony CMOS sensor
Effective Pixels	1280 x 1024
Scanning System	Progressive
Electronics Shutter Speed	Auto( 1/25,1/30~1/10000s )
Min . Illumination	0.01Lux/F1.2 (Colour), 0.001 Lux/F1.2 (B/W)
S/N Ratio	>50db
<b>Camera Features</b>	
Day/Night	Color / B / W
Backlight Compensation	BLC / HLC / WDR(digital)
White Balance	Auto
Gain Control	Auto
Noise Reduction	2D , 3D
Privacy Masking	Up to 4 Area
<b>Lens</b>	
Focal Length	2.6mm, 4mm , 6mm or 8mm
Max Aperture	F1.4
Focus Control	Manual
Angle of View	97° ~ 67°
Lens Type	Fixed Iris (Fixed lens)
Mount Type	Board -in Type
<b>Video</b>	
Compression	H.264 High Profile, Main Profile, Baseline / MJPEG
Resolution	1280x1024, 1280x720, 640 x320 , 160x112
Frame Rate	Preferred Stream : 1280x720, 1280x720 (1~25/30fps)
	Alternate Stream : 640x 320, 320x160, 160x112 (1~25/30fps)
Bit Rate	32KB ~ 16KB Mbps , support VBR , CBR
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPV4/IPV6, HTTP, TCP/IP, UDP, RTP, RTCP,UPNP, RTSP, SMPT, NTP, DHCP, DNS, PPPoE , DDNS, FTP
ONVIF	ONVIF Ver.2.0
Max .User Access	10 users
Smart Phone	iPhone, iPad , Android , Symbian
<b>Auxiliary Interface</b>	
Memory Slot	Micro SD , Max 64GB
<b>General</b>	
Power Supply	DC12V, POE (802.3af)
Power Consumption	≤ 5W
Temperature	-20°C ~ 60°C
Protection	IP66
Dimension	107 mm x 53.4 mm
Weight	0.5 KG

