

CP-NB20-R

Full HD@25fps Box IP Camera



Main Features

- Progressive Scan CMOS Sensor
- Full HD 1080p / HD 720p real-time at dual streaming
- Motion Detection
- Privacy Masks
- Day/Night ICR (optional)
- Auto Iris Lens support
- Micro SD support
- BNC analog output

Specifications

Image Sensor	1/2.7" Progressive CMOS
Minimum Illumination	0.2 lux @ F 1.2
Shutter Speed	1 ~ 1/10000 sec.
White Balance	Manual / AWB / ATW
Lens	C/CS mount Lens
Video Compression	H.264/MJPEG
Video Streaming	Simultaneous H.264 + H.264
Resolution	H.264 : Full HD 1080p/HD 720p/SXGA/D1/VGA/QVGA/CIF, MJPEG : Full HD 1080p/HD 720p/SXGA/D1/VGA/QVGA/CIF
Frame Rate	HD 25/30 fps, Full HD 25 fps
Digital Zoom	Support
Motion detection	On/Off
Privacy Mask	Support
Privacy Mask Type	Transparent, Color
ICR	Auto/On/Off
Tampering Alarm	On/Off
Audio	Line out, Line in/mic in
Audio Compression	G.711/G.726
Alarm IN	5V 10K ohm Pull up
Alarm Out	Photo Relay Output 300VDC/AC
Event Notification	HTTP, FTP, SMTP
Multiple Languages	English, French, German, Italian, Korean, Simplified Chinese, Russian
Interface	10/100Mbps Ethernet (RJ-45), RS485
Protocol	IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF
Password Levels	User and Administrator
Security	HTTPS, IP Filter, IEEE 802.1X
Internet Browser	Internet Explorer (6.0+), Chrome, Firefox, Safari
User Account	20
Micro SD	SDHC support
Audio Connector	Stereo phone jack, Ø 3.5mm
Auto Iris	DC Drive
Analog Video	1.0 Vp-p / 75 Ω, BNC
Operating Temperature	0°C ~ 50°C (32° ~ 122° F)
Humidity	Humidity: 10% to 90%, No Condensation
Power Source	DC12V/PoE
Power Consumption	4.5W
Regulatory	CE, FCC, RoHS Compliant
Dimension	125 x 82 x 52 mm (L x W x H) (w/o lens)
Weight	330 g (0.73 lbs)