

CP-NT20VL3-R

Full HD@25fps Vari-Focal Bullet IR IP Camera



Main Features

- Progressive Scan CMOS sensor
- Full HD 1080p / HD 720p real-time at dual streaming
- H.264 and MJPEG compression
- Built-in IR Illuminator (effective distance: 30m)
- Motion Detection
- Privacy Masks
- Micro SD support
- Sun Shield & Cable Management

Specifications

Image Sensor	1/2.7" Progressive CMOS
Minimum Illumination	Fl.4 0 lux (IR LED on)
Shutter Speed	1 ~ 1/10000 sec.
White Balance	Manual / AWB / ATW
Lens	3.3 ~ 12 mm
Video Compression	H.264/MJPEG
Video Streaming	Simultaneous H.264 + H.264
Resolution	H.264 : Full HD 1080p/HD 720p/SXGA/D1/VGA/QVGA/CIF, MJPEG : Full HD 1080p/HD 720p/SXGA/D1/VGA/QVGA/CIF
Frame Rate	HD 25/30 fps, Full HD 25 fps
Digital Zoom	Support
Motion detection	On/Off
Privacy Mask	Support
Privacy Mask Type	Transparent, Color
ICR	Auto/On/Off
Tampering Alarm	On/Off
Audio	Line out, Line in/mic in
Audio Compression	G.711/G.726
Alarm IN	5V 10 K ohm Pull up
Alarm Out	Photo Relay Output 300VDC/AC
Event Notification	HTTP, FTP, SMTP
Multiple Languages	English, French, German, Italian, Korean, Simplified Chinese, Russian
Interface	10/100Mbps Ethernet (RJ-45)
Protocol	IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF
Password Levels	User and Administrator
Security	HTTPS, IP Filter, IEEE 802.1X
Internet Browser	Internet Explorer (6.0+), Chrome, Firefox, Safari
User Account	20
IR	23Pcs LEDs, Upto 30 Mtrs
Micro SD	SDHC support
Audio Connector	Stereo phone jack, Ø 3.5mm
Operating Temperature	10° ~ 50°C (14° ~ 122° F)
Humidity	Humidity: 10% to 90%, No Condensation
Power Source	DC12V/PoE/AC24V
Power Consumption	9W
Weatherproof Standard	IP66
Regulatory	CE, FCC, RoHS Compliant
Dimension	Ø 84 x 180 mm (Ø 3.3 x 7.1 inches) with Sunshield: Ø 84 x 193 mm (Ø 3.3 x 7.6 inches)
Weight	940 gm (2.07 lbs)