



Pioneers in Security



## HD SDI Camera Outdoor 30 Mtr



### FEATURES

The range is a simple yet solid camera unit designed for shorter range applications. The cameras come with a fixed lens and are ready to install out of the box. Suitable for retail, small commercial, domestic or lower-cost installations, the range is for installers requiring an entry-level camera with performance and reliability. Broadcasting pictures with OSD controller



OSD  
CONTROLLER

HD SDI  
Sony Super  
HAD II CCD

Model	S - 2002 SDI (420 TVL)	S - 2004 SDI (520 TVL)
Type	Colour/Monochrome	
Signal System	PAL	
CCD	1/3" Sony Colour	
Picture Elements	537 (H) x 597 (V)	795 (H) x 596 (V)
Resolution	420 TVL	520 TVL
Minimum Illumination	0 Lux (IR LED ON)	
Vertical Frequency	50Hz	
Horizontal Frequency	15.625KHz	
Clock Frequency	28.375MHz	
Scanning System	2:1 Interlace	
S/N Ratio	≥4 dB	≥50dB
Electronic Shutter	1/50-1/100,000S	
Lens	3.6 mm	6 mm
White Balance	AUTO Tracking	
Back Light Compensation	ON	
Auto Gain Control	ON	
Gamma	0.45	
Video Output	1V p-p, 75Ω	
Power Supply	DC12V ±10%	
Current Consumption	220mA (MAX)	
IR Effect Distance	15m (Outdoor)	20m (Outdoor)
OSD Controller	Yes	

