



Pioneers in Securities



S-IP01 / S-IP02 H.264 IP IR Camera Outdoor

FEATURES

- Radiant distance up to 20m / 30m
- True H.264 Realtime Video Compression
- Full D1 Resolution 720x 480 (NTSC) / 720 s 576 (PAL) in live monitoring
- High Quality ED Glass Lense
- IP66 Weather Rating
- Automatic activate LED : Below 10Lux
- Support Network Protocol: HTTP, TCP/IP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE
- **P2P Remote Access**



S-IP01 (20 Mtr)



S-IP02 (30 Mtr)

Sony Super HAD II CCD

Specification	S- IP 01 (20 Mtr.)	S- IP 02 (30 Mtr.)
Video/audio compression standard	H.264 Main Profile/ADPCM	
Image Sensor	1/3"Sony Super HAD II CCD	
Gain Control	Auto	
White Balance	Auto	
Min. Illumination	0.005Lux	
Infrared range	20m	30m
Frame Rate	D1:(PAL: 1 - 25fps, NTSC : 1-30fps)	
Network protocle	HTTP, TCP/IP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE	
network	Cable network: a RJ-45 10M / 100M adaptive	
WIFI	Optional	
3G	Optional	
Audio in	1	
Audio out	1	
Video out	1* BNC	
RS485	1	
Power Supply	DC12V	
Power Consumption	<5W	
Working Environment	-10°C~ +60°C, 10%~90%	
CMX Software	64 Channel	
Lens	3.6 mm (6 / 8 mm optional)	

