

Features:


- 1/3" Sony Ex-view HAD II CCD
- Built-in 2.8~12mm, 2MP IR Lens
- Built-in OSD, ICR
- 2 Nos of IR LED Array
- 50m IR Distance (Smart IR)

- Adjustable IR Illumination
- 3-Axis Vertical / Horizontal / Rotational
- Smart Mechanical Structure Design
- Full Metal Body Vandal-proof
- Water Resistance IP 66

Specifications:

| Model | BE-P7050SB-V2812 |
|--------------------------|--|
| Sensor | 1/3" Sony Ex-view HAD II CCD |
| DSP | Sony Effio-P |
| Effective Pixel | 976(H) x 582(V) |
| Resolution | 700TVL |
| Lens | 2.8~12mm, 2MP IR Lens |
| Viewing Angle | 92° ~ 27.2° |
| Min-Illumination | 0.01Lux @ F1.2 (Col), 0.0002 Lux (B&W) |
| Electronic Shutter | Auto / Manual |
| OSD | Yes, Aavailable |
| Sync | Internal |
| IR LED | 2 Nos of IR Array LED |
| IR Range | 50 meter |
| S/N Ration | >52dB (AGC OFF) |
| Electronic-Shutter Speed | 1/50 ~ 1/100,000s |
| BLC | Off / BLC / HLC |
| Day/Night | IR Cut-filter with Auto Switch |
| Weather Proof | IP 66 |
| Bracket | 3-Axis Concealed Cable Bracket |
| Voltage | DC 12V |
| Current | <500mA |
| Video Output | 1.0Vp-p/75 ohm |
| Dimension | 259.6 mm × 109mm x 111.8mm |
| Operate Temperature | -20°C ~ +50°C |
| Weight | 996.5g |







www.markglobal.in