

BE - P7120SD-V2812
700TVL, 20m Indoor IR Dome Camera



Features :

- 1/3" Sony Ex-ViewHAD II CCD
- Built-in 2.8~12mm, 2MP IR Lens
- Built-in easy OSD, ICR
- 42 Nos of 3mm IR LED
- 20m IR Distance (Smart IR)
- Optical Grind Glass with Special coating
- 3-Axis Vertical /Horizontal / Rotational
- Video-Out for Installation
- Isolated LED for heat Insulation
- Indoor Dome Camera

Specifications :

Model	BE-P712SD-V2812
Sensor	1/3" Sony Ex-view HAD II CCD
DSP	Sony Effio-P
Effective Pixel	976(H) x 582(V)
Resolution	700TVL
Lens	2.8~12mm, 2MP IR Lens
Viewing Angle	92° ~ 27.2°
Min-Illumination	0.01Lux @ F1.2 (Col), 0.0002 Lux (B&W)
Electronic Shutter	Auto / Manual
OSD	Yes, Aavailable
Sync	Internal
IR LED	42 Nos of 3mm IR LED
IR Range	20 meter
S/N Ration	>52dB (AGC OFF)
Electronic-Shutter Speed	1/50 ~ 1/100,000s
BLC	Off / BLC / HLC
Day/Night	IR Cut-filter with Auto Switch
Bracket	3-Axis Concealed Cable Bracket
Voltage	DC 12V
Current	<550mA
Video Output	1.0Vp-p/75 ohm
Dimension	106.5 mm Dia × 109.3 (H)
Operate Temperature	-20°C ~ +50°C
Weight	460g

