

## Outdoor Waterproof IR Camera

### Features

- Built-in High Intensity 52 IR-LED.
- Dual Window Structure to Prevent Reflection.
- Diffusion of Infrared Light.
- Built-in Board Lens.
- 3-Axis Mechanism for Brackets optional in packages.
- Supports functions: AES, AGC, AWB, and BLC.



### Specifications



MODEL	HF-L6
Image Sensor	1/3" Color Sony Super HAD II CAD
Pixels	PAL: 512 (H) X 582 (V); NTSC: 512 (H) X 492 (V)
Resolution	480 TVL
Min. Illumination	0.5 LUX/F1.2
S/N Ratio	More than 50dB
Electronic Shutter	1/60~1/100,000 sec
Iris Control	Manual
Lens	6mm /8mm lens optional
Gamma Correction	0.45
Scanning System	PAL 625 Lines, 50 Field/S; NTSC 525 Lines, 60 Field/S
White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Compensation	Auto
IR	IR Range of 45m with 52 LEDs
Sync	Internal Sync
Video Output	1.0Vp-p75Ω, Negative
Power Consumption	DC12V, 250mA
Operating Temperature	-10°C~+50°C RH95% Max