## PCD-C28N2

## High Resolution IR Dome Camera





## **Key Features**

- o 1/3" Digital Image Sensor
- o 700 TVL High Resolution
- o 0.3 lux
- o COP Function
- o 3.6 mm lens
- o IR Range of 20 Mtr. with 24 Leds
- o AGC, AWB and BLC
- o CE, FCC and RoHS Certified













## **SPECIFICATIONS**

Image Sensor 1/3" Digital Image Sensor

Pixels PAL:762(H)x504(V)

Resolution 700 TVL
Min. Illumination 0.3 Lux

S/N Ratio more than 52dB

Electronic Shutter PAL:1/50~1/100,000 sec

Lens 3.6 mm Lens

Gamma Correction >0.45 ( AGC OFF )

White Balance (AWB) Auto
Gain Control (AGC) Auto
Back Light Compensation Auto

IR Range of 20 Mtr. with 24 Leds

Sync Internal

Video Output  $1.0 \text{Vp-p} / 75 \Omega$ Power Supply DC12V, <40mA Dimensions 92(R)×75(H)mm

Weight 0.26kg

Operating Temperature  $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$ ,  $14^{\circ}\text{F} \sim 122^{\circ}\text{F}$ 

Certifications CE, FCC, RoHS