PCD-C32N2-G High Resolution IR Dome camera - 20Mtr.



Key Features

- o Digital Image Sensor
- o 850 TVL High Resolution
- o ~~ 0.01 lux Min Illumination
- o 3.6mm Lens
- o IR Range of 20 Mtr. with 24 Leds

∞PinnAcle

- o AGC, AWB, BLC
- o CE, FCC and RoHS Certified



SPECIFICATIONS

| Image Canada | Divided Images Conneg |
|-------------------------|--|
| Image Sensor | Digital Image Sensor |
| Pixels | PAL:976(H)×582(V), NTSC: 976(H)×494(V) |
| Resolution | 850 TVL |
| Min. Illumination | 0.01 lux |
| S/N Ratio | more than 50dB |
| Electronic Shutter | 1/60-1/100,000sec |
| Flickerless Mode | Electrical |
| Lens | 3.6mm Lens |
| Gamma Correction | 0.45 |
| White Balance (AWB) | Auto |
| Gain Control (AGC) | Auto |
| Back Light Compensation | Auto |
| IR | IR Range of 20 Mtr. with 24 Leds |
| Sync | Internal |
| Power Supply | DC12V |
| Power Consumption | DC12V, 250mA |
| Dimensions | Φ90mm x 75mm |
| Weight | 200 gms |
| Operating Temperature | -10~ +50° RH95% Max |