

# CP-SY22C-ET

Day & Night 22x Optical Zoom Speed Dome camera



## Main Features

- 1/4" SONY Super HAD CCD
- 22 X optical zoom
- Manual speed 0.01°~500°/S, Preset speed 500°/S
- 360° continuous pan rotation, 90° tilt rotation, auto flip
- Pan 0.01°~180° /S, Tilt 0.01°~120° /S, Preset: 500° /S
- Timing activation function
- Programmable 220 preset positions
- 4 pattern tours, each one 180s memory
- 8 cruising tracks, each cruising track has 32 preset positions
- 6 alarm inputs and 2 outputs
- 8 privacy zones
- The dome will rotate back to preset position after a period of vacant time
- RS-485 multiple protocols, Pelco\_P, Pelco\_D compatible
- IP66-rated waterproof
- Build-in fan and heater, temperature auto control.
- Outdoor wall mount housing

## Specifications

Image Sensor	1/4" SONY Super HAD CCD
Resolution	460 TVL
S/N Ratio	More than 48dB
Electronic Shutter	1/50 ~ 1/10,000
Iris Control	DC Auto
Zoom Optical	22 X
Lens	4 mm-88mm
Focus Mode	Auto/Manual
White Balance (AWB)	Auto/Manual
Gain Control (AGC)	Low/Medium/High/Off
Special Functions	OSD, Auto Cruise, Auto Scan
Pan Range	360°continuous pan rotation
Pan Speed	0.01°~ 180° /S
Tilt Range	90°(Auto Flip)
Tilt Speed	0.01°~ 120° /S
Proportional Pan/Tilt Control	Yes
Number of Presets	220
Preset Speed	500°/S
Surge Protection	Yes
Alarm	6 alarm inputs and 2 outputs
Fan & Heater	Build-in fan and heater
Communication	RS-485
Sync. System	Internal synchronization
Power Supply	AC24V±10%
Power Consumption	Indoor : 10W Outdoor : 30W
IP Rating	IP66
Operating Temp	Indoor : (0°C ~ +50°C ) Outdoor: (-35°C ~ +55°C )