



QMXO-P10T

Professional Mini Outdoor Speed Dome Camera (QMXO Series/10x)

Compact, Reliable and Easy to use



1. Fast & Silent Motion

- No Accumulative Error with Preset Function
- Shortest Path By Vector Drive Technology
- High Accuracy with Micro-Stepping Control Technology
- Smooth Motion at High Zoom Magnification Mode
- Lighting Speed (max 360⁰/Sec) & Smooth Manual Speed (MIN. 0.05⁰/Sec)
- Lowest Noise & Lowest Vibration
- Endless 360⁰/Sec Pan Rotation

2. Superior Zoom Camera

- 100x Zoom Control (Optical 10x, Digital 10x), WDR
- Day & Night (IR Cut-filter)

3. Powerful Functions

- Independent Preset Characteristic Setup (AE, WB and etc)
- 128 Preset Positions with Alphanumeric Labels
- 4 Patten, 8 Swing and 8 Group Functions
- 4 Privacy Zones (Spherical Coordinates)
- Auto Flip, Auto Parking, Power-up Action
- On Screen Display On/Off
- Built-in Sensor In/Out Function (4 In / 2 Out)
- 4.5\" - Small in Size
- Vandal-Proof (Dome Cover : PC / Housing & Accessories : AL)
- Optional Network Function (IP Addressable)

www.markglobal.in

Specifications:

Model	QMXO-P10C		
Signal Format	PAL		
Camera	Image Device	Sony 1/4" Interline Transfer CCD	
	Total Pixel	470K Pixels [795(H) x 596(V)]	
	Effective Pixel	440K Pixels [752(H) x 582(V)]	
	H. Resolution	500 TV Lines(Color), 570 TV Lines(B/W)	
	S/N Ratio	50dB (AGC Off)	
	Zoom	10x Optical Zoom and X10 Digital Zoom	
	Focal Length	F1.8, f=3.8 ~ 38mm	
	MIN. Illumination	0.7 Lux (Color) / 0.02 Lux (B/W) @ 50 IRE	
	Day & Night	Auto / Day / Night (IR Cut Filter)	
	Focus	Auto / Manual / Semi-Auto	
	Iris	Auto / Manual	
	Shutter Speed	128x ~ 1/120000 sec	
	AGC	Normal / High / Off	
	White Balance	Auto / Manual (Red & Blue Gain Adjustable)	
	BLC	Low / Middle / High / Off	
	Flickerless	Selectable	
	SSNR	Low / Middle / High / Off	
	Other Functions	Frame Freeze Function, System Image Flip by Installation Type	
Pan/Tilt	Range	Pan : 360°(Endless)	
		Tilt : 180°(Auto-Flip On) , 95°(Auto-Flip Off)	
	Pan/Tilt Speed	Preset : 360° sec	
		Manual : 0.05°~ 360° sec (Zoom Proportional)	
		Swing : 1°~ 180° sec	
	Preset	128 Presets with Labels / Independent Preset Characteristic Setup	
	Pattern	4 Patterns (Approx. 5 Minutes for Each Pattern)	
	Swing	8 Swings	
Group	8 Groups (MAX. 20 Entries for Each Group)		
Other Functions	Image Auto Flip, Auto Parking, Power-up Action & etc.		
General	Communication	RS-485	
	Protocol	Pelco-D, Pelco-P Selectable	
	Privacy Zone	4 Zones	
	Sensor In/Out	Built-in 4 Input	
	OSD	English On / Off	
	Fan/Heater	Built-in	
	Power	DC Type : DC 12V / 2.5A(Default)	
		AC Type : AC 24V / 1.5A(Optional)	
	Dimension	Dome : ø 115 mm / 4.5"	
		Housing : 190(ø) x 263(H) x 297(W) mm / 7.5" (ø) x 10.4" (H) x 11.7"(W)	
Weight	Approx. 3.8 Kg / 8.4 Lbs		
Operating Temp.	-30°C ~ 50°C / -22°F ~ 122°F		