



QDK-2200

Keyboard Controller

PTZ Controller for CCTV

SPECIFICATIONS

Model	QDK-2200
Keyboard Communication	Interface: RS-485 (Tx 3 Port, Trx 1 Port)
	Pan/Tilt operating distance: 4700 ft(1029m) No 24 AWG wire
	Protocol: Multiple(Pelco-d, etc.)(Baud rate selectable)
Connector Type Data	Terminal Block(8p)
Keyboard Keypad	Rubber Button Numeric Keypad and Camera Function Key
Joystick	Stick 3-axis, variable speed with zoom
Input Voltage	12V DC or 9V batt (Battery mode)
Power Consumption	Max. 140mA
LCD Display	Graphic display: 16*2 Graphic display
Operating Temperature	0 to 45
Humidity	10% ~ 7% non-condensing
Dimension & Weight	280(W) x 174(D) x 92(H), Net: 0.7kg, Gross: 1.7kg
Packing Include	Keyboard, Adaptor
	Packing include: Batt 9V(Alkaline), USB Cable, Manual, Terminal Block(8p)

*Design and specifications are subject to change without notice.

FEATURES

- » Economical Controller
- » Any DVR with Mouse Function
- » RS-485 Redundancy
- » Small Sized
- » Battery Powered
- » Recalls up to 256 Cameras from One Keyboard.
- » Multiple Protocol Supported in Each Channel
- » Programmable User Preferences (Preset, Tour, Group, etc.)
- » User Password Support

DESCRIPTION

- » Controls camera functions such as pan, tilt, zoom, and focus.
- » Sets and calls camera preset positions
- » Activates pre-programmed group presets, tour and pattern sequences.
- » The LCD is used to display current status as well as to provide a menu system for setting operational parameters.

DIMENSIONS

