


Key Features

- o H.264 standard compression format
- o 32 Ch. CIF full Real Time
- o Free DDNS Supported
- o 3G Dongle Supported
- o Support 4 SATA HDD/ 3 SATA + 1 DVD/RW, 3 USB2.0
- o HDMI/TV(BNC)/VGA/ synchronous video output
- o Easy Backup : U-disk/Hard disk/USB CD/DVD-RW/Download
- o Support Window Mobile, iPhone, iPad, Android, Blackberry, Symbian and 3G
- o Support six operations at the same time, recording, playback, network transmission, backup, mobile monitoring, PTZ control etc.



SPECIFICATIONS

Processor	High performance embedded microprocessor
Operating System	Embedded LINUX
System Resources	Pentaplex: Live recording, Playback, Backup, Remote access, Mobile monitoring
User Interface	GUI
Control Devices	Front panel, USB mouse, IR remote control, Keyboard, Network
Video Input	32 x BNC,(1.0Vp-p,75Ω)
Video Output	1 BNC,(1.0Vp-p,75Ω),1VGA,HDMI 1080P
Video Standard	NTSC 720F/S,PAL600F/S
Compression	H.264
Video Resolution	1280*1024
Video Recording	32Ch@CIF
Video Display Split	1/4/8/9/16/24
Audio Input	8×RCA
Audio Output	1 ×RCA
Alarm Input	4 Channel
Alarm Output	1 Channel
Hard Disk	4 SATA or 3 HDD + 1 DVD/RW (Max. 2TB)
Recording Mode	Manual, schedule(regular continuous), MD(Video detection: Motion detection, Video blank, video loss, Alarm)Stop
Recording Priority	Manual>Alarm>Motion Detection
Search Mode	Time/date, Alarm, Motion Detection
Playback	32Ch
Backup Mode	U-Disk/Hard disk/USB CD/DVD-RW/Download
Interface Ports	3 USB, 1 RS485, 1 RJ45
3G	3G Dongle Supported
Protocols	TCP/IP,UDP,DHCP,DNS,IP filter, PPPOE, E-mail, Alarm server, UPNP, DDNS, DNS Binding

SPECIFICATIONS

Remote Operations	Monitor, Playback, System setting, files download, Log information
Power Supply	112V/6A
Power Consumption	≤30W
Working Temp	-10°C~+55°C/10~90%RH/86~106KPa
Dimensions	440mm x 400mm x 70mm
Weight	3.8kg(Without HDD)