

DS-9508/9516NI-S Embedded NVR



Key Features

- Third-party network cameras supported
- Up to 5 Megapixels (2560×1920) recording resolution.
- 8 SATA interfaces
- One button archive
- HDD group management



Specifications

	DS-9508NI-S	DS-9516NI-S
Video/Audio input		
IP Video input	8-ch 4CIF/4-ch 720P/2-ch UXGA realtime, or 4-ch UXGA/2-ch 5 Megapixels not real time	16-ch 4CIF/8-ch 720P/4-ch UXGA real time, or 8-ch UXGA/4-ch 5 Megapixels not real time
Hard disk		
Type	8 SATA interfaces	
Capacity	Up to 2TB capacity for each disk	
External interface		
Network interface	1,RJ-45, 10/100/1000Mbps self-adaptive Ethernet interface	
Serial interface	1 RS-232 interface (for parameters configuration, maintenance , transparent channel);1 RS-485 interface (for PTZ control);1 RS-485 keyboard interface (for special keyboard control)	
USB interface	2, USB2.0	
Alarm in	16	
Alarm out	4	
General		
Power supply	100~240 VAC, 6.3A, 50~60Hz	
Consumption	≤20W (without hard disk or DVD-R/W)	
Working temperature	-10 °C ~ +55 °C	
Working humidity	10%~90%	
Chassis	19-inch rack-mounted 2U chassis	
Dimensions (W x D x H)	450 x 470 x90 mm	
Weight	≤ 8kg (without hard disk or DVD-R/W)	

Rear Panel of DS-9516NI-S



1. Reset
2. RS-232 serial interface
3. LAN (10/100/1000Mbps self-adaptive utp ethernet interface)
4. eSATA backup/extended Storage interface(optional)
5. RS-485 matched resistance switch
6. RS-485 serial interface, alarm in, alarm out
7. GND
8. 100~240 VAC power input