CP-CRC-L34E



IR Illuminator Camera Housing – 30 Meter

Main Features



- \Rightarrow Accurate Constant Circuit drive develops excellent performance of LED, high efficiency and long service life
- \Rightarrow Full Light for night vision camera
- \Rightarrow Indoor/Outdoor use
- \Rightarrow Easy Installation

Feature	Specification
Quantity of LEDs	2PCS High Power 2W IR LEDs
Wavelength	850nm
Diameter of lens frame	φ34mm
Day/night Switch	Auto
Protection Level	IP66
Working Voltage	DC12V
Inside Space for Camera	L140mm*W100m*H80mm
Power Consumption	9W
Working Temperature	-30°C-+50°C
Dimension	140*100*320mm
Weight	0.6KG
Certification	CE

Feature	Specification
Time Task	Auto activation of Preset/Scan/Tour/ Pattern by preset-time
Communication	RS485
Sync. System	Internal / External (V-sync.)
Video Output	CVBS: 1.0Vp-p / 75Ω
Power Supply	6-12 V DC (Recommendation : DC9 V)
Power Consumption	2.4 W (3.4 W, motor active)
IP Rating	IP66 all-environments protection, 3000V thunder-proof
Operating Temp	-10°C ~ +50°C (14°F ~ 122°F)
Certifications	CE, FCC and RoHS