



Active System Integration

CP-MY22CL10-E

Horizontal Resolution of 540 TVL

www.asi.ind.in



Features

- 1/4" Sony Ex-View HAD CCD
- Horizontal Resolution of 540 TVL
- 22x Optical Zoom
- 3.6mm (6mm optional)
- Wide Tilt range: +45°~-90°
- IP 66 weather proof
- CE, FCC and RoHS Certified

Technical Specification

Model	CP-MY22CL10-E
Image Sensor	1/4" Sony Ex-View HAD CCD
Pixels	PAL: 795Hx596V, NTSC: 768Hx494V
Resolution	540 TVL
Minimum Illumination	0.7 lux@F1.2
S/N Ratio	more than 50dB
Electronic Shutter	1/50(1/60) - 1/100000 Sec
Iris Control	Yes
Zoom Optical	22x
Zoom Digital	12x
Lens	3.9~85.8 mm
Focus Mode	Auto/Manual
Gamma	0.45



Active System Integration

www.asi.ind.in

Technical Specification

White Balance (AWB)	ON/OFF Selectable
Gain Control (AGC)	ON/OFF Selectable
Back Light Comp.	ON/OFF Selectable
Day & Night (ICR)	Yes
IR LED	High Power LED
Night Vision Range	100 mtrs
Special Functions	OSD, Camera Title, Mirror, Privacy Mask=8, Anti Vibration Housing, Auto Scan, Auto Cruise, Pattern
Pan Range	360 ° Continuous
Pan Speed	0.1°/s ~ 60°/s
Tilt Range	90° ~ 45°
Proportional Pan/Tilt Control	Yes
Number of Presets	80
Surge Protection	Yes
Alarm	Yes
Fan & Heater	Yes



Active System Integration

www.asi.ind.in

Fan & Heater	Yes
Communication	RS 485, Protocol: Pelco-P/D, Baud Rate: 2400~19200 bps
Sync. System	Internal
Video Output	1.0 Vp-p/75W
Power Supply	AC24V+/-25% / DC12V
Power Consumption	60W
IP Rating	IP66
Dimensions	400 x 320 x 280
Weight	11.0 Kg
Operating Temp	-35~60 °C
Certifications	CE/FCC