



Active System Integration

## CP-UAP-SC23CB

Horizontal Resolution of 540 TVL

www.asi.ind.in



### Technical Specification

Image Sensor	1/4" High Quality Image Sensor
Pixels	640(H) × 480(V)
Resolution	540 TVL
Minimum Illumination	0.5 Lux@F1.6
S/N Ratio	more than 50dB
Electronic Shutter	1/50(60)s ~1/100,000s
Zoom Optical	23x
Lens	3.9 ~ 89.7 mm
Focus Mode	Auto / Manual
White Balance (AWB)	Auto, ATW, Indoor, Outdoor, Manual
Gain Control (AGC)	Auto/Manual
Back Light Comp.	BLC
Day & Night (ICR)	Auto(ICR) / Color / B/W

### Features

- 1/4" High Quality Image Sensor
- High Resolution of 540 TVL
- Powerful 23x optical zoom
- Day/Night (ICR), 2D-DNR, Auto iris, Auto focus, AWB, AGC, BLC
- Max 300 °/s pan speed, 360° continuous pan rotation
- Up to 255 presets, 5 auto scan, 8 tour, 5 pattern



Active System Integration

www.asi.ind.in

## Technical Specification

Special Functions	Day/Night (ICR), 2D-DNR, Auto iris
Pan Range	0° ~ 360° endless
Pan Speed	0.1° ~ 250°/s
Idle Motion	Activate Preset/Pan/Scan/Tour/Pattern if there is no command in the specified period
Tilt Range	0° ~ 90°, auto flip 180°
Tilt Speed	0.1° ~150°/s
Power up Action	Auto restore to previous PTZ and lens status after power failure
Time Task	Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time
Number of Presets	255
Preset Speed	Pan: 300°/s; Tilt:200°/s
Alarm	2/1 channel In/Out
Communication	RS485
Sync. System	Interlacing
Video Output	BNC(1.0Vp-p/75Ω), PAL / NTSC
Power Supply	AC24V/1.5A (±10%), DC12V optional
Power Consumption	12W
Dimensions	Φ170mm×155mm
Weight	1.5KG
Operating Temp	-10°C ~ 50°C / Less than 90% RH