



Active System Integration

## CP-UAP-SC23CL10

Horizontal Resolution of 540 TVL



www.asi.ind.in

### Technical Specification

Image Sensor	1/4" High Quality Image Sensor
Pixels	PAL: 640(H) × 480(V)
Resolution	540 TVL
Minimum Illumination	0.5 Lux/F1.6, 0 Lux(IR ON)
S/N Ratio	more than 50dB
Electronic Shutter	1/50(60)s ~ 1/100,000s
Zoom Optical	23x
Lens	3.9 ~ 89.7 mm
Focus Mode	Auto / Manual
Gamma	0.45
White Balance (AWB)	Auto, ATW, Indoor, Outdoor, Manual
Gain Control (AGC)	Auto/Manual
Back Light Comp.	BLC
Day & Night (ICR)	Auto(ICR) / Color / B/W

### Features

- 1/4" High Quality Image Sensor
- High Resolution of 540 TVL
- Min. Illumination of 0.5 Lux/F1.6, 0 Lux(IR ON)
- Powerful 23x Optical Zoom
- DWDR, Day/Night (ICR), 2D-DNR, Auto iris, Auto focus, AWB, AGC, BLC
- Up to 255 Preset, 5 Auto Scan, 8 Tour, 5 Pattern



Active System Integration

www.asi.ind.in

## Technical Specification

Special Functions	Day/Night (ICR), 2D-DNR, Auto iris, Auto focus, AWB, AGC, BLC
Pan Range	Pan Range 0° ~ 360° endless
Pan Speed	0.1° ~ 160°/s
Idle Motion	Activate Preset/Pan/Scan/Tour/Pattern if there is no command in the specified period
Tilt Range	-15° ~ 90°, auto flip 180°
Tilt Speed	0.1° ~ 120°/s
Power up Action	Human-oriented focal length/ speed adaptation
Time Task	Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time
Number of Presets	255
Preset Speed	Pan: 300°/s; Tilt:200°/s
Communication	RS485
Sync. System	Interlacing
Video Output	BNC(1.0V <sub>p-p</sub> /75Ω), PAL / NTSC
Power Supply	AC24V/3A (±10%), DC12V optional
Power Consumption	15W, 28W(IR on, Heater on)
IP Rating	IP66
Dimensions	Φ186mm×234mm
Weight	5.0kg
Operating Temp	-40°C ~ 60°C