



Active System Integration

CP-UAP-SC23CL6

Horizontal Resolution of 600 TVL

www.asi.ind.in



Features

- 1/4" CMOS
- High Resolution of 600TVL
- Min. Illumination of 0.5Lux@F1.6
- Powerful 23x Optical Zoom
- Day/Night (ICR), 2D-DNR, , Auto iris, Auto focus, AWB, AGC, BLC
- Up to 255 Preset, 5 Auto Scan, 8 Tour, 5 Pattern

Technical Specification

Image Sensor	1/4" CMOS
Pixels	PAL: 640H) × 480(V)
Resolution	600 TVL
Minimum Illumination	0.5 Lux@F1.6
S/N Ratio	more than 50dB
Electronic Shutter	Auto: 1/s~1/100,000s Manual: 1/s~1/10,000s
Zoom Optical	23x
Lens	3.9 ~ 89.7 mm
Focus Mode	Auto
Gamma	0.45
White Balance (AWB)	Auto/Manual
Gain Control (AGC)	Auto/Manual
Back Light Comp.	ON/OFF
Day & Night (ICR)	Yes



Active System Integration

www.asi.ind.in

Technical Specification

Special Functions	Day/Night (ICR), 2D-DNR, Auto iris, Auto focus, AWB, AGC, BLC
Pan Range	Horizontal: 0°~360°endless, Vertical: -15°~90° auto flip 180° to continue monitor
Tilt Range	Horizontal: 0°~360°endless, Vertical: -15°~90° auto flip 180° to continue monitor
Number of Presets	255
Preset Speed	Horizontal: 240° /s, Vertical: 200° /s
Surge Protection	Yes
Communication	RS485
Video Output	CVBS: 1.0Vp-p / 75Ω
Power Supply	AC 24V/2.2A (±10%)
Power Consumption	13W(Indoor), 31W(Outdoor, heater on)
IP Rating	IP66
Dimensions	Φ185(mm) x 299(mm)
Weight	5.0kg
Operating Temp	-40°C ~ 60°C
Certifications	CE, FCC and RoHS