



Active System Integration

CP-UAP-SC23CP

Horizontal Resolution of 540 TVL

www.asi.ind.in



Technical Specification

Image Sensor	1/4" High Quality Image Sensor
Pixels	640(H) × 480(V)
Resolution	540 TVL
Minimum Illumination	0.5 Lux/F1.6
S/N Ratio	more than 50dB
Electronic Shutter	1/50(60)s ~1/100,000s
Zoom Optical	23x
Lens	3.9 ~ 89.7 mm
Focus Mode	Auto / Manual
White Balance (AWB)	Auto, ATW, Indoor, Outdoor, Manual
Gain Control (AGC)	Auto/Manual
Back Light Comp.	BLC
Day & Night (ICR)	Auto(ICR) / Color / B/W

Features

- 1/4" High Quality Image Sensor
- High Resolution of 540 TVL
- Min. Illumination of 0.5 Lux/F1.6
- Powerful 23x Optical Zoom
- DWDR, Day/Night (ICR), 2D-DNR, Auto iris, Auto focus, AWB, AGC, BLC
- Up to 255 Preset, 5 Auto Scan, 8 Tour, 5 Pattern



Active System Integration

www.asi.ind.in

Technical Specification

Special Functions	Day/Night (ICR), 2D-DNR, Auto iris, Auto focus, AWB, AGC, BLC
Pan Range	0° ~ 360° endless
Tilt Speed	0.1° ~ 160°/s
Power up Action	Auto restore to previous PTZ and lens status after power failure
Time Task	Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time
Number of Presets	255
Preset Speed	Pan: 300°/s; Tilt:200°/s
Communication	RS485
Sync. System	Interlacing
Video Output	BNC(1.0Vp-p/75Ω), PAL / NTSC
Power Supply	AC24V/3A (±10%), DC12V optional
Power Consumption	12W, 27W(Heater on)
IP Rating	IP66, IK10 optional
Dimensions	Φ186mm×234mm
Weight	2kg
Operating Temp	-40°C ~ 60°C / Less than 90% RH