



Active System Integration

## CP-LAC-TC62L2A

High Resolution of 620 TVL

www.asi.ind.in



### Technical Specification

Image Sensor	High Quality Image Sensor
Pixels	PAL:640H x 480V
Resolution	620 TVL
Minimum Illumination	0.2 lux, 0 lux (IR ON)
S/N Ratio	More than 47dB
Iris Control	Manual
Lens	3.6 mm Lens
Gamma Correction	0.45
White Balance (AWB)	Auto
Gain Control (AGC)	Auto

### Features

- High Quality Image Sensor
- 620 TVL High Resolution
- 0.2 lux @ F1.2, 0 lux (IR ON)
- 3.6 mm Lens
- IR Range of 20 Mtr with 19 IR Leds
- AGC, AWB and BLC



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

Back Light Comp.	Auto
Day & Night (ICR)	Auto
IR	IR Range of 20 Mtr. with 19 IR Leds
Sync	Internal Sync
Video Output	1.0Vp-p/75ohm
Power Supply	DC 12V
Power Consumption	170mA (145-196mA)
IP Rating	IP66
Dimensions	169mm(L) x 80mm(H) x 70mm(W)
Weight	265g
Operating Temp	-10°C~50°C, -20°C~60°C
Certifications	CE, FCC and RoHS