



Active System Integration

## CP-QAC-DC62L2H2

High Resolution of 620 TVL

www.asi.ind.in



### Features

- High Quality Image Sensor
- 620 TVL High Resolution
- 0.2 lux @ F1.2
- 3.6 mm Lens
- IR Range of 20 Mtr with 24 IR Leds
- AGC, AWB and BLC

### Technical Specification

|                      |                                 |
|----------------------|---------------------------------|
| Image Sensor         | High Quality Image Sensor       |
| Pixels               | PAL:752H×582V<br>NTSC:768H×494V |
| Resolution           | 620 TVL                         |
| Minimum Illumination | 0.01 lux @F1.2                  |
| S/N Ratio            | More than 50dB                  |
| Electronic Shutter   | 1/60-1/100,000sec               |
| Flickerless Mode     | Electrical                      |
| Lens                 | 3.6 mm Lens                     |
| Gamma Correction     | 0.45                            |
| White Balance (AWB)  | Auto                            |



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

|                    |                                    |
|--------------------|------------------------------------|
| Gain Control (AGC) | Auto                               |
| Back Light Comp.   | Auto                               |
| Day & Night (ICR)  | Auto                               |
| IR                 | IR Range of 20 Mtr with 24 IR Leds |
| Sync               | Internal Sync                      |
| Power Supply       | DC 12V                             |
| Power Consumption  | DC12V, 250mA                       |
| Weight             | 200g                               |
| Operating Temp     | -10~ +50°C RH95% Max               |
| Certifications     | CE, FCC and RoHS                   |