



Active System Integration

## CP-QAC-DC60VAL2-Q

High Resolution of 600 TVL

www.asi.ind.in



### Technical Specification

Image Sensor	1/3" High Quality Image Sensor
Pixels	PAL:752H×582V NTSC:768H×494V
Resolution	600 TVL
Minimum Illumination	0.01 lux @F1.2
S/N Ratio	more than 50dB
Electronic Shutter	1/50(60)-1/100,000sec
Flickerless Mode	Electrical
Lens	4-9 mm auto Iris Vari-Focal Lens
Gamma Correction	0.45

### Features

- 1/3" High Quality Image Sensor
- 600 TVL High Resolution Camera
- lux @ F1.2
- 3.6 mm Fixed Lens
- IR Range of 20 mtr with 22 LEDs
- AGC, AWB and BLC



Active System Integration

www.asi.ind.in

## Technical Specification

White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Comp.	Auto
Day & Night (ICR)	Yes
IR	IR Range of 20 mtr with 22 LEDs
Sync	Internal Sync
Power Supply	DC12V±5%
Power Consumption	DC12V,350mA
Dimensions	127mm(w)x91mm(h)
Weight	410g
Operating Temp	-10~ +50°C RH95% Max
Certifications	CE, FCC and RoHS