



Active System Integration

CP-QAC-TC60L2-D

High Resolution of 600 TVL

www.asi.ind.in



Technical Specification

Image Sensor	1/3" High Quality Image Sensor
Pixels	PAL:752H×582V NTSC:768H×494V
Resolution	600 TVL
Minimum Illumination	0.01 lux @F1.2
S/N Ratio	more than 50dB
Electronic Shutter	1/50(60)-1/100,000sec
Flickerless Mode	Electrical
Lens	3.6 mm
Gamma Correction	0.45

Features

- 1/3" High Quality Image Sensor
- 600 TVL High Resolution Camera
- lux @ F1.2
- 3.6 mm Lens
- IR Range of 20 mtr with 24 LEDs
- AGC, AWB and BLC



Active System Integration

www.asi.ind.in

Technical Specification

White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Comp.	Auto
Day & Night (ICR)	Yes
IR	IR Range of 20 mtr with 24 LEDs
Sync	Internal Sync
Power Supply	DC12V±5%
Power Consumption	DC12V,350mA
IP Rating	IP66
Dimensions	145mm(L)X58mm(h)x60mm(w)
Weight	500g
Operating Temp	-10~ +50°C RH95% Max
Certifications	CE, FCC and RoHS