



Active System Integration

## CP-SAC-DC60L2

High Resolution of 600 TVL

[www.asi.ind.in](http://www.asi.ind.in)



### Technical Specification

Image Sensor	1/3" High Quality Image Sensor
Pixels	PAL:762(H)x504(V)
Resolution	600 TVL
Minimum Illumination	0.3 Lux
S/N Ratio	0.1 Lux@F1.2, 0 Lux (IR ON)
Electronic Shutter	1/50(1/60) - 1/100000 sec
Lens	3.6 mm
Gamma Correction	0.45(AGC OFF)

### Features

- 1/3" High Quality Image Sensor
- 600 TVL High Resolution Camera
- Lux@F1.2, 0 Lux (IR ON)
- 3.6 mm Fixed Lens
- IR Range of 20Mtr. with 24 IR LEDs
- AGC, AWB and BLC



Active System Integration

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Comp.	Auto
IR	IR Range of 20Mtr. with 24 IR LEDs
Sync	Internal Sync
Video Output	CVBS:1.0Vp-p/75Ω Composite
Power Supply	DC12V±5 %
Power Consumption	≤6W
Dimensions	(Φ)92.5 x 76H mm
Weight	0.23kg
Operating Temp	-10°C ~ 50°C
Certifications	CE, FCC and RoHS