



Active System Integration

CP-RAC-TC72L3

High Resolution of 720 TVL

www.asi.ind.in



Technical Specification

Image Sensor	High Quality Image Sensor
Pixels	PAL:765H×510V
Resolution	720 TVL
Minimum Illumination	0.1 lux @F1.2(IR on)
S/N Ratio	more than 46.4db
Electronic Shutter	1/50 - 1/100000 sec
Lens	3.6 mm
Gamma Correction	0.45

Features

- High Quality Image Sensor
- 720 TVL High Resolution Camera
- Lux@F1.2(IR on)
- 6 mm Fixed Lens
- IR Range of 30 mtr with 36 IR LEDs
- IP66, AGC, AWB and BLC



Active System Integration

www.asi.ind.in

Technical Specification

White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Comp.	Auto
IR	IR Range of 30 Mtr with 36 IR Leds
Sync	Internal Sync
Video Output	1.0Vp-p / 75Ω
Power Supply	DC12V
Power Consumption	DC12V 280 mA IR ON
IP Rating	IP66
Dimensions	145(L) x 72(W) x 62(H) mm
Weight	385g
Operating Temp	-10C ~ 50C, 14°F ~ 122°F
Certifications	CE, FCC and RoHS