



Active System Integration

## CP-QAC-TY54ML5

540 High Resolution Camera

www.asi.ind.in



### Technical Specification

Image Sensor	1/3" SONY Super HAD II CCD
Pixels	PAL:500 (H)x582(V)
Resolution	540 TVL
Minimum Illumination	0 LUX/F1.2(IR ON)
S/N Ratio	more than 50 dB
Electronic Shutter	1/60-1/100,000sec
Flickerless Mode	Electrical
Lens	6 mm
Gamma Correction	0.45

### Features

- 1/3" SONY Super HAD II CCD
- 540 TVL High Resolution Camera
- 0 LUX/F1.2(IR ON)
- IR Range of 30M with 36 IR LEDs
- 6 mm Lens
- OSD, D-WDR, 2D-DNR, Motion Dection, Privacy Masking, Mrror, AWB, AGC, BLC



Active System Integration

www.asi.ind.in

## Technical Specification

White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Comp.	Auto
IR	IR Range of 50M with 63 LEDs
Sync	Internal Sync
Video Output	Composite 1.0V P-P/75Ω
Special Functions	OSD, D-WDR, 2D-DNR, Motion Detection, Privacy Masking, Mirror
Power Supply	DC12V±10%
Power Consumption	DC12V,400mA
IP Rating	IP66
Weight	450g
Operating Temp	-10~ +50°C RH95% Max
Certifications	CE, FCC and RoHS