



Active System Integration

## CP-QAC-TY65MVBA5

650 TVL High Resolution Camera

[www.asi.ind.in](http://www.asi.ind.in)



### Features

- 1/3" Sony Super HAD II
- 650 TVL High Resolution
- 0.01 Lux Min.Illumination
- 2.8-12 mm Lens
- Array Range of 50Mtr. with 4 array LED Pcs.
- OSD, AGC, AWB and BLC
- CE, FCC and RoHS Certified

### Technical Specification

Model No	CP-QAC-TY65MVBA5
Image Sensor	1 / 3" SONY Super HAD II
Pixels	PAL: 752 (H) ×582 (V) ; NTSC: 768 (H) ×494 (V)
Resolution	650 TVL
Min.Illumination	0.01 Lux
S/N Ratio	More than 50 dB
Electronic Shutter	1/60-1/100,000 Sec
Flickerless Mode	Electrical
Iris Control	Manual
Lens	2.8-12 mm Lens
Gamma Correction	0.45
White Balance (AWB)	Auto
Gain Control (AGC)	Auto



Active System Integration

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

Back Light Compensation	Auto
IR	IR Range of 50 Mtr with 4 Array IR LEDs
Video Output	1.0 Vp-p/75 ohm
Special Functions	OSD
Power Supply	DC 12V
Power Consumption	DC 12V, 400 mA
Dimensions	Φ96mm x 315mm(L)
Weight	450g
Operating Temperature	-10~ +50°C RH95% Max
Certifications	CE, FCC, RoHS