



Active System Integration

## CP-EAC-VY65MVFL3

High Resolution of 650 TVL

www.asi.ind.in



### Technical Specification

Image Sensor	1/3" Sony Super HAD II
Pixels	PAL:752Hx582V, NTSC:768Hx494V
Resolution	650 TVL
Min. Illumination	0 lux @F1.2
S/N Ratio	more than 48dB
Electronic Shutter	1/50(1/60) - 1/100000 Sec
Flickerless Mode	ON/OFF
Lens	4~9mm Vari-focal Auto Iris Lens
Focus Mode	Manual
Gamma Correction	0.45
White Balance (AWB)	Auto

### Features

- 1/3" Sony Super HAD II
- 650 TVL High Resolution Camera
- 0 lux @ F1.2 (IR ON)
- 4~9 mm Vari-Focal Auto Iris Lens
- IR Range of 30 Mtrs with 30 Blue LEDs
- AGC, AES, BLC, HLC, Mirror, Privacy Masking and
- Sens Up, 2D-DNR, 3D-DNR, LSC, DIS and Eclipse
- CE, FCC and RoHS Certified



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Compensation	ON/OFF Selectable
High Light Compensation	Yes
IR	30 Blue LEDs, Upto 30 Mtrs
WDR	No
Sync	Internal/External Line Lock
Video Output	1.0 Vp-p/75 ohm
Special Functions	OSD, Camera ID, Camera Title, Mirror, Privacy Masking=7, Motion Detection=4, Sens-Up(Low Shutter)=x256, 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE
Power Supply	DC12V±5%
Power Consumption	< 4W
Dimensions	100mmx150mm
Weight	900g
Operating Temperature	-10~50 °C
Certifications	CE, FCC,RoHs