



Active System Integration

## CP-EAC-TY70MVFL5W-E

High Resolution of 700 TVL

www.asi.ind.in



### Technical Specification

Image Sensor	1 / 3" Sony Super HAD II CCD
Pixels	PAL:752(H)x582(V), NTSC:768(H)x494(V)
Resolution	700 TVL
Min. Illumination	0 lux @F1.2
S/N Ratio	more than 48dB
Electronic Shutter	1/50(1/60) - 1/100000 Sec
Lens	4~9 mm Vari-Focal Auto Iris Lens
Focus Mode	Manual
Gamma Correction	0.45
White Balance (AWB)	On/Off Selectable
Gain Control (AGC)	On/Off Selectable

### Features

- 1/3" Sony Super HAD II
- 700 TVL High Resolution Camera
- 0 lux @ F1.2 (IR ON)
- 4~9 mm Vari-Focal Auto Iris Lens
- IR Range of 50 Mtrs with 72 LED's
- AGC, AES, BLC, HLC, Mirror, Privacy Masking and Motion Detection
- Sens Up, WDR, 2D-DNR, 3D-DNR, LSC, DIS and Eclipse
- Weather Resistant IP 66 Housing



Active System Integration

www.asi.ind.in

## Technical Specification

Back Light Compensation	On/Off Selectable
IR	72 LEDs, Upto 50 Mtrs
Sync	Internal/External Line Lock
Video Output	1.0 Vp-p/75 ohm
Special Functions	OSD, Camera ID, Camera Title, Mirror, Privacy Masking=8, Motion Detection=4, Sens-Up(Low Shutter)=x256, 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE
Power Supply	DC 12V $\pm$ 5%
Power Consumption	< 12W
IP Rating	66
Dimensions	260mm x 185mm x 100mm
Weight	1500g
Operating Temperature	-20~50°C
Certifications	CE, FCC, RoHs