



Active System Integration

CP-QAC-DY70ML2H2

High Resolution of 700 TVL

www.asi.ind.in



Technical Specification

Image Sensor	1/3" Sony CCD Sensor
Pixels	PAL:752(H)×582(V), NTSC:768(H)×494(V)
Resolution	700 TVL
Min. Illumination	0.01 Lux
S/N Ratio	more than 50dB
Electronic Shutter	1/60-1/1,00,000sec
Flickerless Mode	Electrical
Lens	3.6 mm Lens
Gamma Correction	0.45
White Balance (AWB)	Auto

Features

- 1/3" Sony CCD Sensor
- 700 TVL High Resolution Camera
- 3.6 mm Lens
- Lux Min. Illumination
- IR Range of 20 mtr with 24 IR LEDs
- AGC, AWB and BLC
- CE, FCC and RoHS Certified



Active System Integration

www.asi.ind.in

Technical Specification

Gain Control (AGC)	Auto
Back Light Compensation	Auto
Day & Night (ICR)	Yes
IR	IR Range of 20Mtr. With 24 IR leds
Sync	Internal Sync
Video Output	1.0 Vp-p/75 ohm
Power Supply	DC12V
Power Consumption	DC12V,270mA
Dimensions	Φ90 x 85mm
Weight	1Kg
Operating Temperature	-10~ +50°C RH95% Max
Certifications	CE, FCC, RoHs