



Active System Integration

## CP-QAC-PY60A

High Resolution of 600 TVL

[www.asi.ind.in](http://www.asi.ind.in)



### Technical Specification

Image Sensor	1/3"Sony Super HAD II
Pixels	PAL:752(H)×582(V), NTSC:768(H)×494(V)
Resolution	600 TVL
Min. Illumination	0.05 lux@F1.2
S/N Ratio	more than 50dB
Electronic Shutter	1/60 - 1/100000 Sec
Lens	3.7 mm
Gamma Correction	0.45
White Balance (AWB)	Auto

### Features

- 1/3"Sony Super HAD II
- 600TVL High Resolution
- lux @ F1.2
- 3.7 mm Pin Hole Lens
- AGC, AWB, BLC
- CE, FCC and RoHS Certified



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

Gain Control (AGC)	Auto
Back Light Compensation	Auto
Sync	Internal
Video Output	1.0 Vp-p/75 ohm
Special Functions	Audio Supported
Power Supply	DC 12V
Power Consumption	DC12V,250mA
Weight	110g
Operating Temperature	-10~ +50°C RH95% Max
Certifications	CE, FCC, RoHs