



Active System Integration

## CP-QAC-PY70MW

High Resolution of 700 TVL



[www.asi.ind.in](http://www.asi.ind.in)

### Features

- 1/3"Sony CCD sensors
- 700TVL High Resolution
- lux Min. Illumination
- 3.7 mm Lens
- AGC, AWB, BLC
- CE, FCC and RoHS Certified

### Technical Specification

Image Sensor	1/3"Sony CCD Sensors
Pixels	PAL:752(H)×582(V), NTSC:768(H)×494(V)
Resolution	700 TVL
Min. Illumination	0.01 Lux
S/N Ratio	more than 50dB
Electronic Shutter	1/60 - 1/100000 Sec
Flickerless Mode	Electrical
Lens	3.7 mm lens
Gamma Correction	0.45



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Compensation	Auto
WDR	Yes
Sync	Internal
Video Output	1.0 Vp-p/75 ohm
Power Supply	DC 12V
Power Consumption	DC12V,100mA
Weight	50g
Operating Temperature	-10~ +50°C RH95% Max
Certifications	CE, FCC, RoHs