



Active System Integration

CP-QMC-Y60ML2

600 TVL Resolution

www.asi.ind.in



Technical Specification

Image Sensor	1/3" Sony Super HAD II CCD
Pixels	PAL:752(H)×582(V), NTSC:768(H)×494(V)
Resolution	600 TVL
Min. Illumination	0.01 lux
S/N Ratio	more than 50dB
Electronic Shutter	1/60-1/100,000sec
Flickerless Mode	Electrical
Iris Control	Manual
Lens	2.8 mm Lens

Features

- 1/3"Sony Super HAD II CCD
- 600TVL Resolution
- Lux Min. Illumination
- 2.8 mm Lens
- IR Range of 20Mtr with 18 LEDs
- OSD, 2D-DNR & LSC supported
- AGC, AWB, BLC



Active System Integration

www.asi.ind.in

Technical Specification

Gamma Correction	>0.45
White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Compensation	Auto
IR	IR Range of 20Mtr. with 18 IR LEDs
Sync	Internal Sync
Video Output	1.0 Vp-p/75 ohm
Special Functions	OSD, 2D-DNR LSC supported
Power Supply	DC12V
Power Consumption	DC12V,250mA
Weight	300g
Operating Temperature	-10~ +50°C RH95% Max
Certifications	CE, FCC, RoHs