



Active System Integration

CP-UAC-PY70M

High Resolution of 700 TVL

www.asi.ind.in



Technical Specification

Image Sensor	1/3" SONY EXview HAD CCD II
Pixels	PAL:752Hx582V, NTSC:768Hx494V
Resolution	700 TVL
Min. Illumination	0.5 lux@F1.2
S/N Ratio	more than 60dB
Electronic Shutter	1/50(1/60) - 1/100000 Sec
Lens	3.6 mm
Gamma Correction	0.45
White Balance (AWB)	Auto

Features

- 1/3" SONY EXview HAD CCD II
- 700 TVL High Resolution Camera
- 0.5 lux @ F1.2
- 3.6 mm Pin Hole Lens
- 2D-DNR, OSD, AWB, AGC, BLC, HLC, ATR, MD, Privacy Masking, Picture Adjustment
- CE, FCC and RoHS Certified



Active System Integration

www.asi.ind.in

Technical Specification

Gain Control (AGC)	Auto
Back Light Compensation	ON/OFF Selectable
Sync	Internal
Video Output	1Vp-p Composite Output (75Ω/BNC)
Special Functions	2D-DNR, OSD, AWB, AGC, BLC, HLC, ATR, MD, Privacy Masking, Picture Adjustment
Power Supply	DC 12V ± 5%
Power Consumption	Max 1.5W
Dimensions	30mm x 30mm x 15.9mm
Weight	50g
Operating Temperature	-30°C~+60°C
Certifications	CE, FCC, RoHs