



Active System Integration

CP-UVR-0400G1-C

H.264 dual stream Video Compression

www.asi.ind.in



Technical Specification

Processor	Embedded processor
Operating System	Embedded LINUX
Two-way Talk	Reuse audio input/output channel 1
User Interface	GUI
Video Input	4 channel, BNC
Video Output	1 HDMI, 1 VGA
Video Standard	NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
Compression	H.264 / G.711
Video Resolution	1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768, 800 × 600
Video Compression	720P HDCVI DVR

Features

- Up to 4 cameras with 1080p Real-time Preview
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- All Channels @720P
- Support 1 SATA HDD up to 4TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB



Active System Integration

www.asi.ind.in

Technical Specification

Video Recording	Main Stream: 1080P(1~12/15fps)/720P/960H/D1/HD1/2CIF/CIF(1~25/30fps), Extra Stream: CIF/QCIF(1~25/30fps)
Video Display Split	1/4
Privacy Masking	4 rectangular zones (each camera)
Motion Detection	Supports
Video Loss	Supports
Camera Blank	Supports
Privacy Masking	4 rectangular zones (each camera)
Hard Disk	1 SATA port, up to 4TB
Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Recording Mode	Manual, Schedule(Regular(Continuous), MD), Stop
Search Mode	Time/Date, MD & Exact search (accurate to second)
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom



Active System Integration

www.asi.ind.in

Backup Mode	USB Device/Internal SATA burner/Network
Interface Ports	1 HDMI, 1 VGA, 2 USB2.0
Max User Account	128 users
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocols	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter
Ethernet	RJ-45 port (10/100M)
Power Supply	DC12V/2A
Power Consumption	10W(without HDD)
Working Temp	-10 ~+55°C / 10~90%RH / 86~106kpa
Dimensions	205mm × 205mm × 40mm
Weight	500g (without HDD)