



Active System Integration

# CP-UVR-0404F4-T

H.264 dual stream Video Compression

www.asi.ind.in



## Technical Specification

Processor	Embedded processor
Operating System	Embedded LINUX
Two-way Talk	1 channel input, 1 channel output, BNC
User Interface	GUI
Video Input	4 channel, BNC
Video Output	2 HDMI, 1 VGA, 1 TV
Video Standard	NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
Video Resolution	1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768, 800 × 600
Video Compression	1080P HDCVI DVR

## Features

- Up to 4 cameras with 1080p Realtime Preview
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- All Channels @ 1080P
- Support 4 SATA HDDs up to 16TB, 1 eSATA up to 16TB, 3 USB2.0, 1CD/DVDRW
- Mobile Software: iCMOB, gCMOB, wCMOB



Active System Integration

www.asi.ind.in

## Technical Specification

Video Recording	Main Stream: 1080P(1~12/15fps)/720P/960H/D1/HD1/2CIF/CIF(1~25/30fps), Extra Stream: CIF/QCIF(1~25/30fps)
Video Display Split	1/4
Privacy Masking	4 rectangular zones (each camera)
Audio Input	4 channel, RCA
Audio Output	1 channel, RCA
Motion Detection	Supports
Video Loss	Supports
Camera Blank	Supports
Alarm Input	4 channel
Alarm Output	6 channel
Hard Disk	4 SATA ports, up to 16TB, 1 eSATA port, up to 16TB
Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Recording Mode	Manual, Schedule(Regular(Continuous), MD), Stop
Search Mode	Time/Date, MD & Exact search (accurate to second)
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

Backup Mode	USB Device/Internal SATA burner/Network
Interface Ports	2 HDMI, 1 VGA, 1 TV, 1 RS485, 1 RS232, 3 USB2.0
Max User Account	128 users
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocols	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter
Ethernet	RJ-45 port (10/100M)
Power Supply	AC 100~240 V, 50/60 Hz
Power Consumption	40W(without HDD)
Working Temp	-10 ~+55°C / 10~90%RH / 86~106kpa
Dimensions	440mm × 410mm ×70mm
Weight	6 Kg.(without HDD)