

CP-UAR-0808P8D

8 Channel 960H H.264 Standalone DVR



Krypto Series

Main Features

- ⇒ Up to 8 cameras with 1080p Realtime Preview
- ⇒ H.264 dual-stream video compression
- ⇒ All channel 960H Realtime Recording
- ⇒ HDMI/VGA / TV simultaneous video output
- ⇒ Support 8 SATA HDD up to 32TB or 6 HDD + 1 CD/DVDRW, 4 USB2.0
- ⇒ Supports 8/3 Ch. Alarm In/Out
- ⇒ Mobile Software: CMOB
- ⇒ CMS Software: KVMS



Feature	Specification
Processor	High performance embedded microprocessor
Operating System	Embedded LINUX
User Interface	GUI
Video Input	8 channel, BNC
Video Standard	NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
Compression	H.264 / G.711
Video Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Video Recording	960H(1~25/30fps)
Extra Stream	CIF/QCIF/D1(1~25/30ps)
Video Display Split	1/4/8/9
Privacy Masking	4 rectangular zones (each camera)
Audio Input	8 channel, RCA
Bi-directional Talk Input	1 channel Input, 1 channel Output(reuse the audio output channel), BNC
Audio Output	1 channel, RCA
Motion Detection	Supports
Video Loss	Supports
Camera Blank	Supports
Alarm Input	8 channel
Alarm Output	3 channel
Hard Disk	8 SATA ports, up to 32TB, 1 eSATA port (Max 4 SATA HDDs), up to 16TB
Smart Phone	iPhone, iPad, Android, Windows Phone

Feature	Specification
CD/DVDRW	yes
Trigger Events	Recording, Tour, Video Push, Email, FTP, Buzzer & Screen tips
Recording Mode	Manual, Schedule(Regular(Continuous), MD), Stop
Search Mode	Time/Date, MD & Exact search (accurate to second)
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Max User Account	20 users
Interface Ports	1 HDMI, 1 VGA, 1 TV, 1 Spot, BNC , 4 USB 2.0, 1 RS232, 1RS485
Ethernet	RJ-45 port (10/100M)
Protocols	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, Alarm Server
Power Supply	AC100~240V, 50/60Hz
Power Consumption	30W
Working Temp	-10 ~ +55°C / 10~90%RH / 86~106kpa
Dimensions	440mm×460mm×89mm
Weight	6.5KG(without HDD)