



Active System Integration

# CP-TAR-3204Q2D

H.264 Dual Stream Video Compression

www.asi.ind.in



## Technical Specification

Processor	High Performance Embedded Microprocessor
Operating System	Embedded Linux
System Resources	Pentaplex function: : Preview, recording, playback, backup, network
User Interface	GUI
Video Input	32 Ch., BNC
Video Output	1 TV Out, 1 Spot, 1 VGA, 1 HDMI
Video Standard	PAL
Compression	H.264

## Features

- Full channel D1 Realtime Recording
- H.264 Dual-Stream Video Compression
- Pentaplex operation: Preview, recording, playback, backup, network
- HDMI / VGA / SPOT / TV Simultaneous Video Output
- Support 2 SATA HDD, 2 USB2.0, 2 RS485, 1 CD/DVDRW
- Multi DVR Client
- Mobile Software: MSS



Active System Integration

www.asi.ind.in

## Technical Specification

Video Resolution	D1/CIF 704*576/352*288(PAL), 704*480/352*240(NTSC)
Video Recording	D1@25fps
Video Display Split	1/4/8/9/16/25/32
Audio Input	4 Ch x RCA
Bi-directional Talk Input	Take up 1CH audio input
Audio Output	1 Ch x RCA
Alarm Input	16 Ch.
Alarm Output	1 Ch.
Hard Disk	SATA x 2, support 3Tb per HDD
CD/DVDRW	Yes
Trigger Events	Record, PTZ move, e-mail, etc
Recording Mode	Manual, Timer, Motion
Search Mode	Time/calendar search, event (motion)
Playback	16 Ch.



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

Interface Ports	1 RJ45 x 1 USB 2.0 x 1 RS485
Max User Account	18 users online, dual stream
Smart Phone	iPhone, Blackberry, Andriod, Windows phone
Protocols	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS
Ethernet	RJ45
Power Supply	DC: 12V
Working Temp	0°C~50°C
Working Humidity	10%~90%
Dimensions	300mm * 270mm * 58mm (W * D * H)