



Active System Integration

CP-TAR-0804Q1

H.264 Video Compression

www.asi.ind.in



Technical Specification

Processor	High Performance Embedded Microprocessor
Operating System	Embedded Linux
System Resources	Pentaplex function: : Preview, recording, playback, backup, network
User Interface	GUI
Video Input	8 Ch., BNC
Video Output	1 TV Out, 1 VGA, 1 HDMI
Video Standard	PAL
Compression	H.264

Features

- Full channel D1 Realtime Recording
- H.264 Dual-Stream Video Compression
- Pentaplex operation: Preview, recording, playback, backup, network
- HDMI / VGA / TV Simultaneous Video Output
- Support 1 SATA HDD, 2 USB2.0, 1 RS485
- Multi DVR Client
- Mobile Software: MSS



Active System Integration

www.asi.ind.in

Technical Specification

Video Resolution	960*576/704*576/352*288(PAL), 960*480/704*480/352*240(NTSC)
Video Recording	D1@(1-25fps)
Video Display Split	1/4/8/9
Audio Input	4 Ch x RCA
Bi-directional Talk Input	Support by taking up 1Ch audio input
Audio Output	1 Ch x RCA
Alarm Input	8 ch
Alarm Output	1 Ch
Hard Disk	SATAx 1, support 2Tb per HDD
Trigger Events	Record, PTZ move, e-mail, etc
Recording Mode	Manual, Timer, Motion
Search Mode	Time/calendar search, event (motion)
Playback	8CH



Active System Integration

www.asi.ind.in

Interface Ports	1 RJ45 x 1, RS485 x 1, USB2.0 x 2
Max user Account	10 users online,dual stream
Smart Phone	iPhone, Blackberry, Andriod, Windows phone
Protocols	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS
Ethernet	RJ45
Power Supply	DC: 12V
Working Temp	0°C~50°C
Working Humidity	10%~90%
Dimensions	300mm * 270mm * 58mm (W * D * H)