



Active System Integration

# CP-UE-01S

H.264 Video Compression

www.asi.ind.in



## Technical Specification

### Features

- 1 Ch. Video Input, 1Ch.Audio output
- H.264 video compression and JPEG image capture
- Full channel @D1 Realtime Encoding
- High Quality Two-Way Talk
- 4 Alarm inputs /2 Alarm outputs
- Support 3G Connection as EVDO(CDMA1X)/WCDMA and etc
- Mobile Software: CMOB
- CMS Software: KVMS

Compression	H.264 / G.711
Video Streaming	H.264 Simultaneously
Video Output	1 channel TV output, BNC(1.0Vp-p, 75Ω)
Resolution	PAL(625Line, 50f/s), NTSC(525Line, 60f/s)
Frame Rete	NTSC : 30 fps@D1 PAL : 25fps@D1
Motion Detection	Zones: 396(22×18), Sensitivity: 1~6 (level 6 is highest)
Privacy Masking	8 self-defined four-sided zones
Snapshot	1~7 f/s JPEG capture
Audio Input	1 channel, 3.5mm JACK MIC IN
Audio Output	1 channel, 3.5mm JACK SPEAK OUT



Active System Integration

www.asi.ind.in

## Technical Specification

Alarm IN	4 channel
Alarm Out	2 Channel
Interface	RJ-45 (10/100Base-T), RS485, RS232
Wireless	3G:EVDO(CDMA1X)/WCDMA and other 3G network
Protocol	HTTP,TCP/IP,ICMP,RTSP,RTP,UDP,RTCP,SMTP,FTP,DHCP,DNS,DDNS,PPPOE
Internet browser	Windows – Microsoft Internet Explorer 6.x or later
Operating Temperature	-30°C ~+55°C
Humidity	10%~90%
Power Source	DC12V
Power Consumption	< 5W
Regulatory	CE, FCC, RoHS Compliant
Dimensions	162mm x136mm x30mm (W x D x H)
Weight	1.0Kg