



Active System Integration

CP-UE-08H2

H.264 Video Compression

www.asi.ind.in



Features

- 8Ch. Video Input, 8Ch. Audio output
- H.264 video compression and JPEG image capture
- Full channel @D1 Realtime Encoding
- High Quality Two-Way Talk
- 8 Alarm inputs /3 Alarm outputs
- 1 HDMI, 2 SATA HDD, 2 USB, 1 RS485 & 1 RS232 interface
- Mobile Software: CMOB
- CMS Software: KVMS

Technical Specification

Processor	Dual-core embedded processor
Operating System	Embedded Linux
Video Input	8 Channel, BNC
Video Output	1HDMI, 1VGA, 1TV, 1Spot BNC(1.0Vp-p, 75Ω)
Compression	H.264 / G.711
Video Resolution	D1/CIF/QCIF/VGA/QVGA
Video Recording	D1/BCIF/CIF/QCIF(1~25/30fps)
Extra Stream	CIF/QCIF
Video Display Split	1/4
Privacy Masking	4 rectangular zones (each camera)
Audio Input	8 Channel
Bi-directional Talk Input	1 Channel



Active System Integration

www.asi.ind.in

Technical Specification

Audio Output	1 channel
Hard Disk	2 SATA
Trigger Events	Recording, PTZ, Tour, Snapshot, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen Tips
Search Mode	Time/Date, Alarm, Motion Detection & Exact search (accurate to second)
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network
Interface Ports	1 HDMI, 2 SATA HDD, 2 USB, 1 RS485 & 1 RS232 interface
Protocols	TCP/IP, PPPOE, DDNS, FTP, IP Filter, DNS, SMTP, NTP, DHCP
Ethernet	RJ-45 (10/100/1000M)
Power Supply	DC12V / 3A
Power Consumption	20W (Exclude HDD)
Working Temp	-10°C ~+50°C / 10%~90% / 86kpa~106kpa
Dimensions	440mm x 300mm x 42.1mm
Weight	2.5Kg