



Active System Integration

## CP-UNC-TP13FL2CD

H.264 Video Compression

www.asi.ind.in



### Technical Specification

|                      |   |
|----------------------|---|
| Image Sensor         | 1/3" 1.3Megapixel CMOS  |
| Minimum Illumination | 0. 1Lux/F1.2 (Color),<br>0.005Lux/F1.2(B/W);0Lux/F1.2(IR on)    |
| Shutter Speed        | Auto/Manual 1/3~1/10000   |
| White Balance        | Auto  |
| AGC Control          | Auto/Manual   |
| Back Light Comp      | Off/BLC/HLC/WDR(128dB)  |
| Lens                 | 2.8~12mm  |
| S/N Ratio            | More than 50dB  |
| Video Compression    | H.264 / MJPEG   |
| Video Streaming      | 1.3M/720P(1 ~ 25/30fps), Sub Stream:<br>D1/CIF(1 ~ 25/30fps)    |
| Video Output         | 1 channel BNC(1.0Vp-p, 75Ω)                                     |
| Resolution           | 1.3M(1280×960) / 720P(1280×720) /<br>D1(704×576) / CIF(352×288) |
| Frame Rate           | 720P(1 ~ 25/30fps)  |
| Privacy Masking      | Up to 4 areas   |

### Features

- 1/3" 1.3 MP Progressive Scan CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1.3M(1280×960)&25/30fps@720P(1280×720)
- 2.8~12mm varifocal lens
- Built-in 2/1 alarm in/out
- Micro SD memory, IP66, PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

## Technical Specification

|                       |  |
|-----------------------|--|
| ICR                   | Auto(ICR)/Color/B/W  |
| Smart Phone           | iPhone, iPad, Android, Windows Phone   |
| Audio Input           | 1 Ch   |
| Audio Output          | 1 Ch   |
| Audio Compression     | G.711a / G.711u(64kbps) / PCM(128kbps)   |
| Alarm IN              | 2 Ch   |
| Alarm Out             | 1 Ch   |
| Protocol              | IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour. ONVIF Ver. 2.0 |
| User Account          | 10 Users   |
| IR                    | 20m  |
| Micro SD              | Micro SD, Max 32GB   |
| Operating Temperature | -10°C~+60°C, 10%~90%   |
| Power Source          | DC12V(AC24 optional), PoE(802.3af)   |
| Power Consumption     | < 10W  |
| Weatherproof Standard | IP66   |
| Regulatory            | CE, FCC and RoHS & UL  |
| Dimension             | φ104mm × 306.7mm   |
| Weight                | 1.25Kg   |