



Active System Integration

CP-UNC-B5142

1000 TVL Resolution Camera

www.asi.ind.in



Technical Specification

Back Light Comp.	BLC / HLC / DWDR
Image Sensor	1/3" 1.3Megapixel CMOS
Minimum Illumination	0.1 Lux@F1.2
Shutter Speed	Auto/Manual, 1/3~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Lens	C/CS Mount Lens
Video Compression	H.264/MJPEG
S/N Ratio	more than 50 dB
Video Streaming	Main Stream:1.3M/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1.3M(1280×960) /720P(1280×720) /D1(704×576) / CIF(352×288)
Privacy Masking	Up to 4 areas

Features

- 1/3" 1.3Megapixel PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1.3M(1280×960)
- DWDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- Max 32GB Micro SD Card for Local Storage
- C/CS Mount Lens
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

Smart Phone	iPhone, iPad, Android, Windows Phone
ICR	Auto(ICR)/Color/B/W
Audio Input	1 Ch
Audio Output	1 Ch
Audio Compression	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	1 Ch
Alarm Out	1 Ch
Interface	1 RS485, 1 RJ45
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	10 Users
Micro SD	Micro SD, Max 32GB
Operating Temperature	-10°C~+60°C, ≤90%
Power Source	DC12V/AC24V, PoE(802.3af)
Power Consumption	< 3.5W
Regulatory	CE, FCC and RoHS
Dimensions	70mm×63.2mm×149.5mm
Weight	650g